HYDRAULIC DRIVE SCISSOR LIFTS

0608 (2132) / 0808 (2732)

Compliant with CE/EAC standards

PRODUCT HIGHLIGHTS

Efficient and Environmentally Friendly

- Small turning radius, flexible operation in narrow spaces
- Standard forklift slot for efficient equipment transportation
- Folding guardrails for easy transport

Reduced Maintenance Costs

- Double-door design for easy maintenance
- Troubleshooting for quick fault diagnosis
- High quality parts and components

More Reliable Performance

- Battery voltage early warning to ensure battery life
- Bumper rail protection
- The pothole protection reporting and horizontal protection system guarantee safety of operation



Standard Features		
2WD×2WS	Maintenance-free battery	Fault diagnosis system
Non-marking tires	Proportional control	Emergency lowering system
Emergency stop	Electrophoretic painting	Tilt protection system
Flashing beacon	Forklift pockets and lifting points	Overload sensing system
Foldable guardrail	Automatic pothole protection	Manual storage box
Drivable at full height	Bumper rails	Auto braking system
Horn & buzzer		
Options & Accessories		
RCBO	AC power to platform	Platform work light
Footswitch	Overhead anti-collision device	Telematics-ready connector

Techno West Verhuur
Heftrucks • Verreikers • Terminaltrekkers • Hoogwerkers

SINOBOOM™

PARTNERS IN ACCESS™


SINOBOOM.COM | SALES@SINOBOOM.COM
NO.128 EAST JINZHOU AV., NINGXIANG HI-TECH INDUSTRY PARK, CHANGSHA, HUNAN, CHINA, 410600


HYDRAULIC DRIVE SCISSOR LIFTS


0608 (2132) / 0808 (2732)

Compliant with CE/EAC standards

Model	0608 (2132)	0808 (2732)
Dimensions		
Max Working Height (Indoor/Outdoor)	8.3 m (27'3")	10.1 m (33'2")
A Max Platform Height (Indoor/Outdoor)	6.3 m (20'8")	8.1 m (26'7")
B Platform Extension	0.9 m (3')	0.9 m (3')
C Length-Stowed	2.39 m (7'10.1")	2.39 m (7'10.1")
D Width-Stowed	0.81 m (2'8")	0.81 m (2'8")
E Height-Stowed (Rails Folded)	1.83 m (6')	1.96 m (6'5")
E Height-Stowed (Rail Unfolded)	2.22 m (7'3.4")	2.35 m (7'8.5")
F Wheelbase	1.85 m (6'0.8")	1.85 m (6'0.8")
Ground Clearance (Pothole Guard Stowed)	0.073 m (3")	0.073 m (3")
Ground Clearance (Pothole Guard Deployed)	0.024 m (0.95")	0.024 m (0.95")
Platform Dimensions (L×W×H)	2.25 m×0.81 m×1.1 m (7'4.6"×2'7.9"×3'7")	2.25 m×0.81 m×1.1 m (7'4.6"×2'7.9"×3'7")
Performance		
Platform Capacity	380 kg (838 lbs)	250 kg (551 lbs)
Extension Platform Capacity	120 kg (265 lbs)	120 kg (265 lbs)
Platform Allowable Occupants (Indoor/Outdoor)	2 persons/1 person	2 Persons(Indoor Only)
Drive Speed (Stowed)	0~3.2 km/ h (0~2 mph)	0~3.2 km/ h (0~2 mph)
Drive-Speed (Raised)	0~0.8 km/ h (0~0.5 mph)	0~0.8 km/ h (0~0.5 mph)
Lift Time (Unloaded)	25 s~30 s	30 s~35 s
Lower Time (Unloaded)	30 s~35 s	34 s~39 s
Gradeability	25%	25%
Max Allowable Inclination (Front-To-Back/Side-To-Side)	3°/1.5°	3°/1.5°
Turning Radius (Inside/Outside)	0 m/2.1 m (0/6'10.7")	0 m/2.1 m (0/6'10.7")
Tire Size/Type	380×125 mm (15×5")/solid	380×125 mm (15×5")/solid
Power		
Drive×Steer	2 WD×2 WS	2 WD×2 WS
Power Source (V/kW)	24 V DC /3.3 kW	24V DC /3.3 kW
Hydraulic Tank Capacity	14L (3.1gal (UK) /3.7gal(US))	14L (3.1gal (UK) /3.7gal(US))
Batteries	24 V,220Ah (Lead Acid Battery)	24 V,220Ah (Lead Acid Battery)
Charger (Input/Output)	100～240 V AC/30A	100～240 V AC/30 A
Weight		
Weight (Indoor/Outdoor)	1,770 kg (3,903 lbs)	1,970 kg (4,344 lbs)(Indoor Only)
Standards Compliance	CE/EAC	







We reserve the right to make specification. The above represents the current specifications at time of publications. 07. 2023